

Z750-450

WHITE FR FLOOR PROTECTION SHEET

A flame-retardant fluted polypropylene sheet for temporary protection of floors, walls, windows, doors, worktops and fitted units during construction, refurbishment and decorating.

The translucent white sheet is approved to LPS 1207 Issue 3 and helps shield finished surfaces from dust, dirt, paint splashes, scuffs and light knocks. It can be cut, curved or creased to suit the area being protected.



Red Readyfix print on translucent white sheet

2.4 x 1.2m SHEET SIZE	2mm THICKNESS	250gsm BASIS WEIGHT
2.88m² COVERAGE	LPS 1207 FR STANDARD	1353a/01 LPCB PRODUCT REF.

FEATURES AND BENEFITS

LPS 1207 APPROVED

LPCB-approved protective covering for construction use.

LIGHTWEIGHT

Quick to handle, position and reposition on site.

EASY TO FIT

Cut, curve or crease with a sharp utility knife.

VERSATILE

Suitable for floors, walls, windows, doors and units.

TRANSLUCENT WHITE

Allows some light through when used over windows.

RECYCLABLE

100% recyclable* where suitable facilities are available.

TECHNICAL SPECIFICATION

PROPERTY	NOMINAL VALUE	TOLERANCE / METHOD	ADDITIONAL INFORMATION
Material / colour	Fluted FR polypropylene / translucent white	Supplier declaration	96% plastic + 4% mineral; FR additive
Sheet size	2400 x 1200mm	Length ±5mm/m; width ±5mm	Coverage 2.88m²; squareness ±5mm/m
Thickness	2.00mm	±0.10mm	Nominal caliper
Basis weight	250g/m²	±5% per sheet; ±10% local	Approx. nominal sheet weight: 0.72kg
Polypropylene density	0.900-0.905g/cm³	ISO 1183	Polypropylene fraction
FR approval	LPS 1207: Issue 3	LPCB certificate 1353a	Approved product reference 1353a/01
Surface / print	Corona treated / red ink	Supplier declaration	Additional Readyfix print assessed and permitted
Euroclass	None stated	No EN 13501 class stated	LPS 1207 approval is a separate classification

INSTALLATION GUIDANCE

1 PREPARE

Make the surface clean, dry and free from grit.

2 LAY

Position sheets to cover the complete work area.

3 CUT

Trim on a sacrificial surface; never cut against the finish.

4 SECURE

Tape joints and edges to reduce movement and trip risk.

HANDLING, STORAGE AND LIMITATIONS

- Store flat in ambient, dry conditions.
- Avoid prolonged direct sunlight, high temperature and humidity.
- For temporary internal use and short-duration external protection only; secure against wind and weather.
- Test tapes on an inconspicuous area before contact with finished or sensitive surfaces.
- Not approved for direct food contact.
- Lay print side up so the required approval marking remains visible.

FIRE STATUS

LPCB approved to LPS 1207 Issue 3 under certificate 1353a, product reference 1353a/01. No Euroclass is stated; confirm that the project specification requires LPS 1207 rather than an EN 13501 classification.

* The sheet is recyclable where suitable facilities are available and the material is clean and correctly sorted. LPS 1207 approval applies to the certified 2.0mm ±5%, 250g/m² ±5% white base material with assessed additional print.

The figures above are based on supplier technical data and are nominal unless a tolerance is shown. This document is guidance only; users must confirm product suitability for the intended surface, fixing method, site conditions and specification.

READYFIX LTD

Croft Street, Preston, Lancashire, PR1 8XD

CONTACT

01772 250060 | sales@readyfixuk.co.uk

ONLINE

readyfixuk.co.uk | Product code Z750-450